

## UHF Narrow Band Multi Channel Transceiver

# STD-302N-R 434MHz

The UHF FM narrow band semi-duplex radio module STD-302 434MHz is suitable for industrial remote control application and telemetry application operated in 434MHz ISM band. SAW filter and narrow band technique provides reliable data communication in industrial application where its interference rejection and practical distance range is required. Switching time and channel selecting time become remarkably faster than conventional transceiver. Suitable for feedback system

### Feature

- 10mW RF power, 3.0V
- Programmable RF channel
- Receiver sensitivity -119dBm
- Excellent vibration & shock resistance / Mechanical durability
- R&TTE (EN 300 220) / RoHS compliance
- FM narrow band

### Application

- Industrial remote control system
- Telemetry system
- Data transmission



### Common

Item	Specification (All ratings at 25 degree C unless otherwise noted)
Communication form	Half-duplex
Frequency	433.050 to 434.775 MHz
Channel step	25kHz Channel programmable (PLL IC: Fujitsu MB15E03)
Frequency stability	+/- 4 ppm (-20 to +60 degree C)
Data rate	9600 bps max. (Pulse width min.100us, max. 15ms)
PLL reference frequency	21.25 MHz (TCXO)
PLL response	30 ms typ. (from PLL setting to LD out)
Supply voltage	3.0 to 5.5 V
Supply current	44 mA (TX) 26 mA (RX)
Operating temp. range	-20 to +60 C (Storage -30 to + 75 C)
TX/RX switching time	15 ms typ. (DI vs valid DO at the same frequency)
Dimension	30 * 50 * 9 mm
Weight	25 g

### Transmitter part

Transmitter type	PLL synthesizer
RF output power	10 mW at 50 ohm
Deviation	2.75 kHz (PN9, 9600 bps)
DI input level	L = GND, H = 3 V to Vcc
Residual FM noise	0.17 kHz
Spurious emission	< -54 dBm (47M - 74M, 87.5M - 118M, 174M - 230M, 470M - 862MHz) < -36 dBm (Other frequencies below 1000 MHz) < -30 dBm (Frequencies above 1000 MHz)
Adjacent CH power	-37 dBm (CH 25 kHz, BW = 16kHz, PN9, 9600bps)

### Receiver part

Receiver type	Double superheterodyne
IF	21.7 MHz (1st), 450 kHz (2nd)
Maximum input level	10 dBm
Receiver sensitivity	-119 dBm (12dB SINAD ) -116 dBm (BER 1%) -110 dBm (0 error / 2556 bits)
Spurious response rejection	80 dB (1st Mix), 60 dB (2nd Mix)
Adjacent CH selectivity	50 dB (+/ 25kHz)
Intermodulation	50 dB (f-200 kHz + f-100 kHz)
Spurious radiation	-57 dBm (below 1000MHz), -47dBm (above 1000MHz)
DO output level	L = GND, H = 2.8V

Specifications are subject to change without prior notice

**CIRCUIT DESIGN, INC.** International Business Division

<http://www.cdt21.com/>  
STD-302N-R 434MHz ver1.0 Apr. 06  
DS\_STD-302N-R-434M\_v10e

7557-1 Hotaka Azumino Nagano 399-8303, Japan  
Tel:+81-263-82-1024 Fax:+81+263-82-1016